



## Data Sheet

### U-TILES Multi-purpose finishing tile

#### COMPOSITION

U-TILES is made up of 1 piece.

#### CHARACTERISTICS

Weight: 0.2 kg

Thickness of the plate: 25 mm

#### MATERIAL

Polypropylene copolymer (PPC)  
 Composition: + / - 80% premium recycled PPC,  
 + / -20% talc + Masterbatch black.  
 Designed and manufactured in Europe.  
 Use of solely recycled materials from Europe.  
 Resistant to bad weather, sea salt, algae and a wide variety  
 of chemicals.  
 Operating temperature: -30°C to +80°C

#### FINISHING

PB-SERIES: Attached using the PB-KIT-8, adds 12 mm to the height of the pedestal.

DPH-Series: Attached using the U-Fix-Plate-1, adds 15 mm to the height of the pedestal.

BC range: attached using the U-Fix-Plate-1, adds 17 mm to the height of the pedestal.

#### PACKAGING

Units per box: 24 pcs

Box weight: 5,16 kg

Box dimensions: 61 x 24 x 24 cm

Boxes per pallet: 64 pcs

Units per pallet: 1536 pcs

Pallet dimensions: 100 x 120 x 220 cm

#### APPLICATIONS

U-Tiles is a multi-purpose finishing accessory. It allows you to lay small finishing patio tiles, either against a wall or side by side. In addition, U-Tiles makes it possible to incorporate smaller tiles into the patio design, allowing creative freedom for a beautiful finish.

#### SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support raised floors for pedestrians only. They cannot support or be subjected to moving or vibrating machines and equipment. This includes cars, maintenance vehicles and other similar equipment.

