



Technical Data Sheet

PB-0-S-TABS 3mm

COMPONENTS

The PB-0-S-TABS 3mm is composed of 1 piece

CHARACTERISTICS

Weight: 0,015 kg Height: 17 mm

MATERIAL

Copolymer polypropylene (CPP)

Composition: +/- 80% first grade pre-selected recycled

PPC, and +/- 20% Talc + Masterbatch black

Designed and manufactured in Europe

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range


of chemicals


Temperature range: -30 °C to +80 °C

PACKAGING

Pieces per carton: 120 pcs Carton weight: 2,10 kg

Carton dimension: 400 x 290 x 150 mm





APPLICATIONS

The PB-0-S-TABS is fixed mechanically by pressure on the PB-0-S18 pedestal. The spacer tabs regulate the spacing between the pavers, ensures alignment, and free water drainage.

The accessory is available for applications with various outdoor finishes, such as granite stone pavers, wood / composite tiles, ceramic tiles and fibreglass or metal grating panels.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other

similar equipment.



SGRP 2017-814