



Technical Data Sheet

U-E10-Wall Shim thickness 1mm

COMPONENTS

The U-E10-Wall is composed of 1 piece.

CHARACTERISTICS

Weight: 0,026 kg Lenght: 175 mm Thickness: 1mm

MATERIAL

Material: SBR

Hardness Shore A Din 53505: 60-80 SHA

Color: Black

Density: 1,55 g/cm3

Temperature range: (-30) +/- 70 °C
Tensile Strenght Din 53504: 3 Mpa
Elongation at break DIN 53504: 250%

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range

of chemicals

PACKAGING

Pieces per carton: 480 pcs Carton weight: 12,70 kg

Carton dimension: 370 x 195 x 120 mm

Cartons per pallet: 108 pcs Pieces per pallet: 51 840 pcs

Pallet dimensions: 80 x 120 x 120 cm

70 mm



APPLICATIONS

The **U-E10 Wall** is a 1 mm shim. Placed on the U-Wall support, it stabilises the paver, provides additional acoustic comfort, and compensates for variations in paver thickness.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

