



Technical Data Sheet

U-E20-Edge Shim thickness 2mm

COMPONENTS

The U-E20-Edge is composed of 1 piece.

CHARACTERISTICS

Weight: 0,042 kg Lenght: 213 mm Thickness: 2mm

MATERIAL

Material: SBR

Hardness Shore A Din 53505: 60-80 SHA

Color: Black

Density: 1,55 g/cm3

Temperature range: (-30) +/- 70 °C
Tensile Strenght Din 53504: 3 Mpa
Elongation at break DIN 53504: 250%

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range

of chemicals

TIS MM TIS MA TIS MA

PACKAGING

Pieces per carton: 240 pcs Carton weight: 10,6 kg

Carton dimension: 250x250x250mm

Cartons per pallet: 60 pcs Pieces per pallet: 14 400 pcs

Pallet dimensions: 80 x 120 x 160 cm



APPLICATIONS

The U-E20 Edge is a 2 mm shim. Placed on the U-Edge support, it stabilises the paver, provides additional acoustic comfort, and compensates for variations in paver thickness.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

Buzon has a policy of continuous improvement and reserves the right to modify, revise or change the above specifications without notice. This technical data sheet is for descriptive purpose only and is based on the product as on the date of publication of this information.