



Technical Data Sheet

U-E20-Wall Shim thickness 2mm

COMPONENTS

The U-E20-Wall is composed of 1 piece.

CHARACTERISTICS

Weight: 0,043 kg

Length: 175 mm

Thickness: 2mm

MATERIAL

Material: SBR

Hardness Shore A Din 53505: 60-80 SHA

Color: Black

Density: 1,55 g/cm³

Temperature range: (-30) +/- 70 °C

Tensile Strength Din 53504: 3 Mpa

Elongation at break DIN 53504: 250%

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range of chemicals

PACKAGING

Pieces per carton: 240 pcs

Carton weight: 10,54 kg

Carton dimension: 370 x 195 x 120 mm

Cartons per pallet: 108 pcs

Pieces per pallet: 25 920 pcs

Pallet dimensions: 80 x 120 x 120 cm

APPLICATIONS

The **U-E20 Wall** is a 2 mm shim. Placed on the U-Wall support, it stabilises the paver, provides additional acoustic comfort, and compensates for variations in paver thickness.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

Buzon has a policy of continuous improvement and reserves the right to modify, revise or change the above specifications without notice. This technical data sheet is for descriptive purpose only and is based on the product as on the date of publication of this information.

BPI 2025 © Copyright Buzon Pedestal International SA.

