



# **Technical Data Sheet**

**U-TABS-2MM** U-Edge Spacer Tab

## **COMPONENTS**

The U-TABS-2MM is composed of 1 piece.

### **CHARACTERISTICS**

Weight: 0,001 kg Height: 17mm

## **MATERIAL**

Copolymer polypropylene (CPP)

Composition: + / -80% first grade pre-selected recycled

PPC, and + / -20% Talc + Masterbatch black

Designed and manufactured in Europe

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range

of chemicals

Temperature range: -30 °C to +80 °C


## **PACKAGING**


Pieces per carton: 1200 pcs Carton weight: 1,57 kg


Carton dimension: 410 x 320 x 95 mm

Cartons per pallet: 180 pcs Pieces per pallet: 216 000 pcs

Pallet dimensions: 100 x 120 x 220 cm







#### **APPLICATIONS**

The Spacer Tabs (U-Tabs) 2mm wide can be used with the U-EDGE. By fixing these in the required location, they create a gap between the paving keeping the smaller cuts evenly spaced and holds them securely in place.

#### **SAFETY INSTRUCTIONS**

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

